




ACCURI CLASSIC™



COLOR REFRACTIVE INDEX (Optional)
80 / 90 / 95
REFLECTOR BEAM
15° / 24° / 40°



ACCURI CLASSIC WHITE

COB [F] 15W / 1410lm /

75mm

D86 x H104 mm

5501 78 3301 01

COB [F] 20W / 1890lm /

100mm

D108 x H128 mm


5501 78 3301 02

COB [F] 30W / 2950lm /

160mm

D168 x H160 mm

5501 78 3301 03



REQUIREMENTS
PSU EXT.
CONNECTED POWER SUPPLY
180 ~ 230 VAC



ACCURI CLASSIC GOLD

COB [F] 15W / 1395lm /

75mm

D86 x H104 mm

5501 78 3301 04

COB [F] 20W / 1860lm /

100mm

D108 x H128 mm


5501 78 3301 05

COB [F] 30W / 2910lm /

160mm

D168 x H160 mm

5501 78 3301 06



REQUIREMENTS
PSU EXT.
CONNECTED POWER SUPPLY
180 ~ 230 VAC



ACCURI CLASSIC BLACK

COB [F] 15W / 1395lm /

75mm

D86 x H104 mm

5501 78 3301 07

COB [F] 20W / 1840lm /

100mm

D108 x H128 mm

5501 78 3301 08

COB [F] 30W / 2950lm /

160mm

D168 x H160 mm

5501 78 3301 09



REQUIREMENTS
PSU EXT.
CONNECTED POWER SUPPLY
180 ~ 230 VAC

