



BETEL PRO™



COLOR REFRACTIVE INDEX (Optional)
80 / 90 / 95
REFLECTOR BEAM
15° / 24° / 40° / 60°
POWER FACTOR
0.9 or above



BETEL PRO + DIM

LED [F] 10W
3000K - 850lm / 6000K-880

92mm
D113 x H57mm

5501 60 2003 10

LED [F] 14W
3000K - 1190lm / 6000K-1190

117-127mm
D143 x H61 mm

5501 50 2003 14

LED [F] 18W
3000K - 1440lm / 6000K-1550

135-145mm
D165 x H63 mm

5501 50 2003 18

LED [F] 20W
3000K - 1600lm / 6000K-1720

167-178mm
D200 x H68 mm

5501 50 2003 20

LED [F] 30W
3000K - 2610lm / 6000K-2820

192-210mm
D230 x H75 mm

5501 50 2003 30

LED [F] 40W
3000K - 3600lm / 6000K-3880

240-255mm
D279 x H94 mm

5501 50 2003 40



BETEL PRO

LED [F] 10W
3000K - 850lm / 6000K-880

92mm
D113 x H57mm

5501 60 2003 10

LED [F] 14W
3000K - 1190lm / 6000K-1190

117-127mm
D143 x H61 mm

5501 50 2003 14

LED [F] 18W
3000K - 1440lm / 6000K-1550

135-145mm
D165 x H63 mm

5501 50 2003 18

LED [F] 20W
3000K - 1600lm / 6000K-1720

167-178mm
D200 x H68 mm

5501 50 2003 20

LED [F] 30W
3000K - 2610lm / 6000K-2820


192-210mm
D230 x H75 mm

5501 50 2003 30


LED [F] 40W
3000K - 3600lm / 6000K-3880

240-255mm
D279 x H94 mm

5501 50 2003 40



REQUIREMENTS
PSU BUILT-IN
CONNECTED POWER SUPPLY
180 - 240 VAC



REQUIREMENTS
PSU BUILT-IN
CONNECTED POWER SUPPLY
180 - 240 VAC

